



506 3/4" Radiator Coupler Adaptor



Connection Size	
Valve to Radiator	N/A
Valve to Pipe	22 mm Compression

Allen Key size	
To adjust Lock-Shield	N/A
To fit Coupler to Radiator	N/A
Allen Keys are not included	

Pressure Ratings	
Max Test Pressure	12 Bar
Max Operating Pressure	10 Bar
Max Differential Pressure	1 Bar
Pressure Drop Value (Kvs)	1.6
Kvs value is the metric measure for the flow of a fully opened valve. It is defined as: The volume flow in cubic metres per hour of water at a temperature of between 5° and 40° Celsius with a pressure drop across the valve of 1 bar.	

Available Finishes - Adaptor	
Antique Brass	Chrome
	Satin Nickel
These valves have a highly polished finish. The unlacquered brass are highly polished as new but will tarnish and age naturally over time.	

Flow Ratings	
Normal Flow Rate	N/A
Max Flow Rate	N/A

Available Finishes - Adaptor	
Old English Brass	Light Pewter
Unlacquered Brass	Pewter
These valves are unlacquered and designed to look old. They are hand finished and appearance may vary from one valve to the next	

Temperature Ratings	
Max Test Temperature	N/A
Max Operating Temperature	N/A
Temperature Adjustment Range	N/A

Disclaimer	
All dimensions are approximate and for roughing in only.	
We reserve the right to alter dimensions without notice.	
We recommend no work be carried out until the goods arrive.	
We can take no responsibility for errors in information supplied.	

